

Akku-Compact Hydraulic Punch

Electric operated hydraulic punch tool with a powerful 18V motor for punching circular, square, and rectangular cutouts in mild and stainless steel.

Features and Specifications:

- Light and easy to handle due to high-tensile aluminium head
- High-performance drive motor with ergonomically-designed 'soft touch' handle
- Overpressure valve
- Weight: 3.7 kg (approximately 8.2 lbs) including battery
- Maximum punching force: 75kN
- Maximum hydraulic pressure: 680 bar
- Battery: Two 18V NiMH batteries
- Battery charging cycles: approx. 500 under normal conditions
- Battery temperature range: 0 to +40°C, capacity loss below 0°C
- Punching circular holes: up to 82mm (approximately 3.2") diameter;

3.0mm (approx. 11 AWG) sheet steel or 2.0mm (14 AWG) stainless steel F=600 N/mm² 89-152mm (approximately 3.5-6.0") diameter*; 2.0mm (14 AWG) sheet steel or 1.5mm

(approximately 16 AWG) stainless steel F=600 N/mm²

Punching shaped holes: 68x68mm (approximately 2.7x2.7") in 3.0mm (approx. 11 AWG) sheet steel or 2.0mm

(14 AWG) stainless steel F=600 N/mm²

92x92mm* (approximately 3.6x3.6") in 2.0mm (14 AWG) sheet steel or 1.5mm (approximately

16 AWG) stainless steel F=600 N/mm² * only with special draw bolt and spacer

Akku-Compact Hydraulic Punch kit 502.631 includes:

- Akku-Compact manual hydraulic tool
- Two 18V NiMH batteries
- 120V battery charger for 18-28V batteries
- Draw bolt 9.5x19mm, 120mm long (approx. 0.37x0.75", 4.7" long)
- Draw bolt 19x19mm, 120mm long (approx. 0.75x0.75", 4.7" long)
- 3 spacer sleeve set
- Pre-drill bit 11mm diameter (approx. 43")
- Heavy duty plastic case



18 Volt/3,0 Ah

Akku-Compact Hydraulic Punch Kit and Spare Parts (Order by Part No.)

www.itcproducts.com

And compact right date ration for and spare rates (order by rate 110.)			
Part No.	Model	Description	
502.631	02070-120V	Akku-Compact Hydraulic Punch kit	
502.635*	02075-120V-T	Akku-Compact Hydraulic Punch kit, with 6 conduit punch & die sets ½"-2"	
502.638	02071-120V	Replacement 18V NiMH battery for Akku-Compact Punch	
502.639	02072-120V	Battery charger 110-130V AC, 60Hz for 18V NiMH battery	

* Special Order

Information subject to change without notice



Akku-Compact Flex Hydraulic Punch

Electric operated hydraulic punch tool with separate punch head and a powerful 18V motor. Akku-Compact Flex punches circular, square and rectangular holes in mild steel and stainless steel.

Features and Specifications:

Light and easy to handle. Separate head makes access to work surfaces easier

Weight: 2.5 kg (approximately 5.5 lbs) including the battery

Maximum punching force: 75kN

Maximum hydraulic pressure: 680 bar

Battery: 18V Li-ion /1.5 Ah

Battery temperature range: -10 to +40°C

Punching circular holes: up to 82mm (approximately 3.2") diameter;

3.0mm (approximately 11 AWG) sheet steel or 2.0mm (14 AWG) stainless steel F=600

 N/mm^2)

89-152mm (approximately 3.5-6.0") diameter*; 2.0mm (14 AWG) sheet steel or 1.5mm (approximately 16 AWG) stainless

steel F=600 N/mm²

Punching shaped holes: 68x68mm (approximately 2.7x2.7") in 3.0mm

(approx. 11 AWG) sheet steel or 2.0mm (14 AWG) stainless steel F=600 N/mm² 92x92mm* (approximately 3.6x3.6") in 2.0mm (14 AWG) sheet steel or 1.5mm

(approximately 16 AWG) stainless steel F=600 N/mm²

* only with special draw bolt and spacer



Akku-Compact Flex Kit 502.641 includes:

- Akku-Compact Flex manual hydraulics
- 18V Li-lon battery
- 120V battery charger for 18-28V batteries
- Draw bolt 9.5x19mm, 120mm long (approx. 0.37x0.75", 4.7" long)
- Draw bolt 19x19mm, 120mm long (approx. 0.75x0.75", 4.7" long)
- 3 spacer sleeve set
- Pre-drill 11mm diameter (approx. 43")
- Heavy duty plastic case



Akku-Compact Flex Kit and Spare Parts (Order by Part No.)

Part No.	Model	Description
502.641	02082-120V	Akku-Compact Flex Hydraulic Punch kit
502.645*	02082-120V-T	Akku-Compact Flex Hydraulic Punch kit, with 6 conduit punch & die sets ½"-2"
502.648	02082-01-120V	Replacement 18V Li-Ion battery for Akku-Compact Flex Punch
502.649	02082-03-120V	Battery charger 110-130V for 18V Li-lon battery

* Special Order

Information subject to change without notice

Printed in Canada: 24-10 EC-1704-2

